

SAFETY DATA SHEET

QUICK EVAPORATING WASH

Page: 1

Compilation date: 06/04/2011

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: QUICK EVAPORATING WASH

Product code: C598

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: ECS Nottingham Ltd
Unit 17
Hazelford Way Industrial Estate
Newstead
Nottingham
NG15 0DQ
United Kingdom

Tel: +44 (0) 1623 720 444

Fax: +44 (0) 1623 720 445

Email: sales@ecsnotts.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 1623 720 444

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xn: R20/21; Xi: R36/37/38; N: R51/53; Xn: R65

Classification under CLP: Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 1: H224; Skin Irrit. 2: H315

Most important adverse effects: Highly flammable. Harmful by inhalation and in contact with skin. Irritating to eyes, respiratory system and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

2.2. Label elements

Label elements under CLP:

Hazard statements: H224: Extremely flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

[cont...]

SAFETY DATA SHEET

QUICK EVAPORATING WASH

Page: 2

Hazard pictograms: GHS02: Flame
GHS08: Health hazard
GHS09: Environmental



Precautionary statements: P243: Take precautionary measures against static discharge.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331: Do NOT induce vomiting.
P370+378: In case of fire: Use Alcohol or polymer foam, Carbon dioxide, Dry chemical powder for extinction.

Label elements under CHIP:

Hazard symbols: Highly flammable.
Harmful.
Dangerous for the environment.



Risk phrases: R11: Highly flammable.
R20/21: Harmful by inhalation and in contact with skin.
R36/37/38: Irritating to eyes, respiratory system and skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 3

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	30-50%

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	T: R46; Xn: R65; -: R10; Xi: R37; N: R51/53	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304	10-30%
-----------	------------	---	---	--------

PROPAN-2-OL

200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
-----------	---------	-------------------------	---	--------

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT.

265-151-9	64742-49-0	F: R11; Xi: R38; N: R51/53; Xn: R65; -: R67	Flam. Liq. 1: H224; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	--	--------

1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-: R10; Xn: R20; Xi: R36/37/38; N: R51/53	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	---	-------

MESITYLENE

203-604-4	108-67-8	-: R10; Xi: R37; N: R51/53	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	----------	----------------------------	--	-------

ISOPROPYLBENZENE

203-132-9	98-82-8	-: R10; Xi: R37	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	---------	-----------------	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 5

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
UK	220 mg/m ³	441 mg/m ³	-	-

PROPAN-2-OL

UK	999 mg/m ³	1250 mg/m ³	-	-
----	-----------------------	------------------------	---	---

1,2,4-TRIMETHYLBENZENE

UK	100 mg/m ³	200 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

MESITYLENE

UK	25 ppm	-	-	-
----	--------	---	---	---

ISOPROPYLBENZENE

UK	125 mg/m ³	375 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Viscosity: Non-viscous

Flash point°C: ~15C

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 7

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1268

14.2. UN proper shipping name

Shipping name: PETROLEUM DISTILLATES, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H224: Extremely flammable liquid and vapour.
H225: Highly flammable liquid and vapour.
H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H315: Causes skin irritation.

[cont...]

SAFETY DATA SHEET
QUICK EVAPORATING WASH

Page: 8

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36: Irritating to eyes.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R46: May cause heritable genetic damage.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.