

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010



Revision: 15.02.2010

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **WASHMAX 40.10 NM 25L**
- **Article number:** 143599
- **Application of the substance / the preparation** Washing fluid for offset printing machines
- **Manufacturer/Supplier:**
FUJIFILM EUROPE NV
EUROPARK-NOORD 21-22
9100 SINT-NIKLAAS
BELGIUM
TEL: +32 3 760 02 00
FAX: +32 3 776 91 22

- FUJIFILM UK LTD
ST MARTINS WAY
ST MARTINS BUSINESS CENTRE
BEDFORD
MK42 OLF
UNITED KINGDOM
- **Further information obtainable from:** productsafety@fujifilm.eu
- **Information in case of emergency:** +32 3 760 02 00

2 Hazards identification

- **Hazard description:**
- 


Xn Harmful
N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- R 10 Flammable.
- R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 65 Harmful: may cause lung damage if swallowed.
- R 66 Repeated exposure may cause skin dryness or cracking.
- R 67 Vapours may cause drowsiness and dizziness.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

(Cont. on page 2)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: WASHMAX 40.10 NM 25L

(Cont. from page 1)

· Dangerous components:

CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy ☒ Xn, ☒ N; R 10-51/53-65-66-67	80-100%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene ☒ Xn, ☒ Xi, ☒ N; R 10-20-36/37/38-51/53	1-5%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ☒ Xn, ☒ Xi; R 10-20/21-38	1-5%
CAS: 26264-05-1 EINECS: 247-556-2	Isopropylamine dodecylbenzenesulfonate ☒ Xn, ☒ Xi; R 22-38-41	0.5-1.5%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene ☒ Xi, ☒ N; R 10-37-51/53	0.5-1.5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Cont. on page 3)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: WASHMAX 40.10 NM 25L

(Cont. from page 2)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

95-63-6 1,2,4-trimethylbenzene

WEL	Long-term value: 125 mg/m ³ , 25 ppm
	ILV

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Cont. on page 4)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: **WASHMAX 40.10 NM 25L**

(Cont. from page 3)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Liquid
Colour:	Yellow
Odour:	Characteristic

· **Change in condition**
Boiling point/Boiling range: 142-200°C

· **Flash point:** 39°C

· **Ignition temperature:** > 200°C

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**
Lower: 0.6 Vol %
Upper: 7 Vol %

· **Vapour pressure at 20°C:** 0.2 kPa

· **Density at 20°C:** 0.785 g/cm³

· **Solubility in / Miscibility with water:** Emulsifiable.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

95-63-6 1,2,4-trimethylbenzene

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

(Cont. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: WASHMAX 40.10 NM 25L

(Cont. from page 4)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1300
- **Packaging group:** III
- **Hazard label:** 3

(Cont. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: WASHMAX 40.10 NM 25L

(Cont. from page 5)

· **Description of goods:** 1300 TURPENTINE SUBSTITUTE

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1300
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** TURPENTINE SUBSTITUTE

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1300
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** TURPENTINE SUBSTITUTE

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful
N Dangerous for the environment

· **Hazard-determining components of labelling:**

mixture of hydrocarbons

· **Risk phrases:**

- 10 Flammable.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 23 Do not breathe vapour
- 24 Avoid contact with skin.

(Cont. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2010

Revision: 15.02.2010

Trade name: WASHMAX 40.10 NM 25L

(Cont. from page 6)

57 Use appropriate container to avoid environmental contamination.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant R-phrases

10 Flammable.

20 Harmful by inhalation.

20/21 Harmful by inhalation and in contact with skin.

22 Harmful if swallowed.

36/37/38 Irritating to eyes, respiratory system and skin.

37 Irritating to respiratory system.

38 Irritating to skin.

41 Risk of serious damage to eyes.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

• Creation Date 13.07.2009**• * Data modified compared to previous version.**